

A32L4160-TRI-SYS COMPONENTS

A3657900

DESCRIPTION

2Look4 160 Closed System - Aluminum Profile Per Meter - Max 3,000mm / 118 1/8"

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling

PHYSICAL

Shape: Rectangle  
Length (mm): 1000  
Length (in): 39 3/8  
Width (mm): 39  
Width (in): 1 5/16  
Height (mm): 31  
Height (in): 1 1/4  
Weight (kg): 0.67  
Weight (lbs): 1.48  
Fixture Material: Aluminum

ELECTRICAL

Driver Included: No

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38477-

DESCRIPTION

2Look4Light 160 System - Bioniq Spot - Profile Insert - 95mm/3 3/4" - 14.5W LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K - Reflectors 20°/40°/60°

GENERAL

Series: Bioniq  
Brand: Prolicht  
Division: Architectural  
Subcategory: Downlight

PHYSICAL

Shape: Round  
Diameter (mm): 95  
Diameter (in): 3 3/4  
Height (mm): 112  
Height (in): 4 7/16  
Min. Recessing Depth (mm): 180  
Min. Recessing Depth (in): 7 1/16  
Light Distribution: Adjustable / Downlight  
Weight (kg): 0.379  
Weight (lbs): 0.836  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum

ELECTRICAL

Input Wattage Range: 10 - 19 W  
Lamp Type: LED (Zhaga Standard)  
Input Wattage (W): 14.5  
Total Output Wattage (W): 13.2  
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac only) and 0-10V Dimming)  
Driver Included: Yes  
Driver Location: External  
Driver Type: Constant Current - Universal  
Driver Class: Class 2  
Input Voltage (V): 120 - 277  
Constant Current (mA): 500

LED

Delivered Lumen Range: 500 - 1999 lm  
Number of LEDs: 1  
Color Temperature (°K): 2700 / 3000 / 3500 / 4000  
Max. Delivered Lumen (lm): 876 / 909 / 955 / 974  
Nominal Lumen (lm): 1304 / 1352 / 1421 / 1450  
CRI: >90 CRI  
Efficiency (%): 88  
Lamp Life (hrs): 50000  
Upon Request: Tunable White Special Color Temperature Special LED


OPTICAL

Reflector°: 20 / 40 / 60  
Adjustability: Rotational 355°; Tilt 30°  
Upon Request: Special Beam Angles

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A32L4160-TRI-SYS COMPONENTS

A38480-

DESCRIPTION

2Look4Light System - Bioniq Spot - 125mm/4 15/16" - 26.4W  
LED (Zhaga Standard) - 2700K / 3000K / 3500K / 4000K -  
Reflectors 18°/36°

GENERAL

Series: Bioniq  
Brand: Prolicht  
Division: Architectural  
Subcategory: Downlight

PHYSICAL

Shape: Round  
Diameter (mm): 125  
Diameter (in): 4 15/16  
Height (mm): 136  
Height (in): 5 3/8  
Min. Recessing Depth (mm): 200  
Min. Recessing Depth (in): 7 7/8  
Light Distribution: Adjustable / Downlight  
Weight (kg): 0.686  
Weight (lbs): 1.512  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /  
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /  
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS /  
ROR  
Fixture Material: Aluminum Die Cast

ELECTRICAL

Input Wattage Range: 20 - 29 W  
Lamp Type: LED (Zhaga Standard)  
Input Wattage (W): 26.4  
Dimming: Tri-Mode (Non-Dimming and Phase Dimming (120Vac  
only) and 0-10V Dimming)  
Driver Included: Yes  
Driver Location: External  
Driver Type: Constant Current - Universal  
Driver Class: Class 2  
Input Voltage (V): 120 - 277  
Constant Current (mA): 700

LED

Delivered Lumen Range: 2000 - 2999 lm  
Number of LEDs: 1  
Color Temperature (°K): 2700 / 3000 / 3500 / 4000  
Max. Delivered Lumen (lm): 2030 / 2080 / 2185 / 2230  
Nominal Lumen (lm): 3210 / 3290 / 3459 / 3530  
CRI: >90 CRI  
Lamp Life (hrs): 50000  
Upon Request: RGB-W Tunable White Special Color Temperature  
Special LED


OPTICAL

Reflector°: 18 / 36  
Adjustability: Rotational 355°; Tilt 30°  
Upon Request: Special Beam Angles

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A32L4160-TRI-SYS COMPONENTS

A38534-

DESCRIPTION

2LOOK4 160 CLOSED - Channel per Meter with Cuts of choice -  
Max 3,000mm / 118 1/8"

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1000  
Length (in): 39 3/8  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA /  
RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP /  
BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS /  
ROR  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE

A32L4160-TRI-SYS COMPONENTS

A38535-

DESCRIPTION

2LOOK4 160 CLOSED - 1,200mm / 47 1/4" - Blank Channel without Holes

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 12.5  
Height (in): 1/2  
Weight (kg): 2.8  
Weight (lbs): 6 3/16  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38536-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 1 Hole - 1200mm / 47 1/4" for Spot - 1 x 95mm / 3 3/4" Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 95mm / 3 3/4" cutout

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38537-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 1 Hole - 1,200mm / 47 1/4" for Spot - 1 x 125mm / 4 15/16" Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 125mm / 4 15/16"

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38538-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 2 Hole - 1,200mm / 47 1/4" for Spot - 2 x 95mm / 3 3/4"Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.664  
Weight (lbs): 5.87  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 2 x 95mm / 3 3/4"

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE





A32L4160-TRI-SYS COMPONENTS

A38539-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 2 Hole - 1,200mm / 47 1/4" for Spot - 2 x 125mm / 4 15/16" Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 2 x 125mm / 4 15/16"

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38540-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 2 Hole Long - 1,200mm / 47 1/4" for Spot - 2 x 95mm / 3 3/4" Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.664  
Weight (lbs): 5.873  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 2 x 95mm / 3 3/4" Holes

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38541-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 2 Hole Long - 1,200mm / 47 1/4" for Spot - 2 x 125mm / 4 15/16" Hole

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 2 x 125mm / 4 15/16"

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38542-

DESCRIPTION

2LOOK4 160 CLOSED - Channel 3 Hole Long - 1,200mm / 47 1/4" for Spot - 3 x 95mm / 3 3/4" Holes

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.664  
Weight (lbs): 5.87  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 3 x 95mm / 3 3/4" Holes

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A38543-

DESCRIPTION

22LOOK4 160 CLOSED - Channel 3 Hole Long - 1,200mm / 47 1/4" for Spot - 3 x 125mm / 4 15/16" Holes

GENERAL

Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1200  
Length (in): 47 1/4  
Width (mm): 165  
Width (in): 6 1/2  
Height (mm): 45  
Height (in): 1 3/4  
Weight (kg): 2.4  
Weight (lbs): 5.29  
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR  
Fixture Material: Aluminum  
Cut-out Measurements: 3 x 125mm / 4 15/16"

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



A32L4160-TRI-SYS COMPONENTS

A3876399

DESCRIPTION

2LOOK4 160 CLOSED - Mounting Frame for Bioniq 95mm/ 3 3/8" Spot

GENERAL

Series: Bioniq  
Subseries: 2Look4 160 Closed System  
Brand: Prolicht  
Division: Architectural

PHYSICAL

Shape: Round  
Diameter (mm): 95  
Diameter (in): 3 3/4  
Height (mm): 23  
Height (in): 7/8  
Weight (kg): 0.129  
Weight (lbs): 0.284  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A32L4160-TRI-SYS COMPONENTS

A3876499

DESCRIPTION

2LOOK4 160 CLOSED - Mounting Frame for Bioniq 125mm / 4 15/16" Spot

GENERAL

Series: Bioniq  
Subseries: 2Look4 160 Closed System  
Brand: Prolicht  
Division: Architectural

PHYSICAL

Shape: Round  
Diameter (mm): 125  
Diameter (in): 4 15/16  
Height (mm): 23  
Height (in): 7/8  
Weight (kg): 0.153  
Weight (lbs): 0.337  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



A32L4160-TRI-SYS COMPONENTS

A3951700

**DESCRIPTION**  
2LOOK4 160 CLOSED - Frame Alignment Kit

**GENERAL**  
Series: 2Look4 160  
Brand: Prolicht  
Division: Architectural  
Mounting Location: Ceiling

**PHYSICAL**  
Shape: Rectangle  
Length (mm): 167  
Length (in): 6 9/16  
Width (mm): 115  
Width (in): 4 1/2  
Height (mm): 25  
Height (in): 1  
Weight (kg): 0.34  
Weight (lbs): 0.75  
Fixture Material: Aluminum

**RATINGS AND CERTIFICATIONS**  
Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE





A32L4160-TRI-SYS COMPONENTS

A39585-

DESCRIPTION
2LOOK4 160 CLOSED - End Component

GENERAL
Series: 2Look4 160
Brand: Prolicht
Division: Architectural

PHYSICAL
Shape: Rectangle
Length (mm): 163
Length (in): 6 <sup>7</sup> / <sub>16</sub>
Width (mm): 38
Width (in): 1 <sup>1</sup> / <sub>2</sub>
Height (mm): 67
Height (in): 2 <sup>3</sup> / <sub>8</sub>
Weight (kg): 0.23
Weight (lbs): 0.51
Fixture Finish: SSR / BKV / CWI / CRY / HAB / LAG / UFT / ITA / RUA / RUR / MIC / FTG / MYG / TWT / LOD / PUS / FRO / FUP / KIA / POP / BLS / SPG / MEY / GOH / GUM / CHC / COM / ABZ / JAG / OBR / MOS / ROR
Fixture Material: Aluminum

ELECTRICAL
Driver Included: No

RATINGS AND CERTIFICATIONS
Certified By: Certified for North American Standards
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



PROJECT
TYPE
NOTES
QUANTITY
DATE

LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)