

A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT
TYPE
NOTES
QUANTITY
DATE

A86324

DESCRIPTION

Brooklyn 50 Aluminum Profile - Trimless - 510mm / 20 1/16" - Aluminum LED frame, Disposable Screen & Diffuser included

GENERAL

Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 510  
Length (in): 20 1/16  
Width (mm): 35  
Width (in): 1 3/8  
Height (mm): 35  
Height (in): 1 3/8  
Light Distribution: Direct  
Weight (kg): 0.38  
Weight (lbs): 0.83  
Installation Requirement: Bolt-Down Installation  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86325

DESCRIPTION

Brooklyn 100 Aluminum Profile - Trimless - 1010mm / 39 3/4" - Aluminum LED frame, Disposable Screen & Diffuser included

GENERAL

Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 1010  
Length (in): 39 3/4  
Width (mm): 35  
Width (in): 1 3/8  
Height (mm): 35  
Height (in): 1 3/8  
Light Distribution: Direct  
Weight (kg): 0.83  
Weight (lbs): 1.829  
Installation Requirement: Bolt-Down Installation  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86326

DESCRIPTION

Brooklyn 200 Aluminum Profile - Trimless - 2010mm / 79 1/8" - Aluminum LED frame, Disposable Screen & Diffuser included

GENERAL

Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 2010  
Length (in): 79 1/8  
Width (mm): 35  
Width (in): 1 3/8  
Height (mm): 35  
Height (in): 1 3/8  
Light Distribution: Direct  
Weight (kg): 1.47  
Weight (lbs): 3.25  
Installation Requirement: Bolt-Down Installation  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86327

DESCRIPTION

Brooklyn 300 Aluminum Profile - Trimless - 3010mm / 118 1/2" - Aluminum LED frame, Disposable Screen & Diffuser included

GENERAL

Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 3010  
Length (in): 118 3/2  
Width (mm): 35  
Width (in): 1 3/8  
Height (mm): 35  
Height (in): 1 3/8  
Light Distribution: Direct  
Weight (kg): 2.20  
Weight (lbs): 4.86  
Installation Requirement: Bolt-Down Installation  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



PROJECT
TYPE
NOTES
QUANTITY
DATE

A86330

DESCRIPTION

Wing Nut - Wall/Ceiling

GENERAL



Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

A86331

DESCRIPTION

Pair of End Components with Screws - Wall/Ceiling

GENERAL

Series: Brooklyn

Brand: Panzeri

Division: Architectural

Mounting Type: Trimless

Mounting Location: Ceiling

Subcategory: Profile

PHYSICAL

Shape: Rectangle

Fixture Finish: WHI



Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86332

DESCRIPTION

Plate for Fixing to Brick - Wall/Ceiling

GENERAL



Series: Brooklyn
Brand: Panzeri
Division: Architectural
Mounting Type: Recessed
Mounting Location: Ceiling
Subcategory: Profile

PHYSICAL

Shape: Rectangle
Fixture Finish: WHI
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS RECESSED

A86334

DESCRIPTION

Reflector - 1000mm / 39 3/8" - Wall - Ceiling - White

GENERAL

Series: Brooklyn

Brand: Panzeri

Division: Architectural

Mounting Type: Recessed

Mounting Location: Ceiling

Subcategory: Profile

PHYSICAL

Shape: Rectangle

Length (mm): 1000

Length (in): 39 3/8

Fixture Finish: WHI



Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE





PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86335

DESCRIPTION

Mounting Plate for Hanging - Wall - Ceiling

GENERAL

Series: Brooklyn

Brand: Panzeri

Division: Architectural

Mounting Type: Recessed

Mounting Location: Ceiling

Subcategory: Profile

PHYSICAL

Shape: Rectangle




Fixture Finish: WHI

Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS RECESSED

A86337

DESCRIPTION

Vertical Angle Connector - 120mm / 4 3/4" - Wall - Ceiling

GENERAL

Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Recessed  
Mounting Location: Ceiling  
Subcategory: Profile


PHYSICAL

Shape: Rectangle  
Length (mm): 120  
Length (in): 4 3/4  
Height (mm): 120  
Height (in): 3/4  
Fixture Finish: WHI  
Fixture Material: Aluminum


RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	



30mm  
(1 3/16")



120mm (4 3/4")

A

A8BROOK-TRI-SYS COMPONENTS RECESSED

PROJECT
TYPE
NOTES
QUANTITY
DATE

A86338

DESCRIPTION

Linear Connector - 120mm / 4 3/4" - Wall - Ceiling

GENERAL


Series: Brooklyn
Brand: Panzeri
Division: Architectural
Mounting Type: Recessed
Mounting Location: Ceiling
Subcategory: Profile

PHYSICAL

Shape: Rectangle
Length (mm): 80
Length (in): 3 1/4
Width (mm): 30
Width (in): 1 3/16
Fixture Finish: WHI
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20



30mm  
(1 3/16")



80mm (3 1/8")

A

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86339

DESCRIPTION

Corner Connector - 90° - 80mm / 3 1/8" - Aluminum - Wall - Ceiling

GENERAL



Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 80  
Length (in): 3 1/8  
Width (mm): 80  
Width (in): 3 1/8  
Height (mm): 35  
Height (in): 1 3/8  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86340

DESCRIPTION

T - Connector - 127mm / 5" - Aluminum - Wall - Ceiling

GENERAL


Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL


Shape: Rectangle  
Length (mm): 127  
Length (in): 5  
Width (mm): 127  
Width (in): 5  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



30mm  
(1 3/16")



127mm (5")



PROJECT	
TYPE	
NOTES	
QUANTITY	
DATE	

A86341

DESCRIPTION

X Connector - 127mm / 5" - Aluminum - Wall/Ceiling

GENERAL



Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

PHYSICAL

Shape: Rectangle  
Length (mm): 127  
Length (in): 5  
Width (mm): 127  
Width (in): 5  
Fixture Finish: WHI  
Fixture Material: Aluminum

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards  
IP rating: IP20



A8BROOK-TRI-SYS COMPONENTS RECESSED

A86342

DESCRIPTION

Power Cables - Brooklyn System - Wall - Ceiling

GENERAL

Series: Brooklyn

Brand: Panzeri

Division: Architectural

Mounting Type: Recessed

Mounting Location: Ceiling

Subcategory: Profile

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards

IP rating: IP20

PROJECT

TYPE

NOTES

QUANTITY

DATE



A8BROOK-TRI-SYS COMPONENTS TRIMLESS

PROJECT
TYPE
NOTES
QUANTITY
DATE

A89116

DESCRIPTION

LED module - 500mm - 8.6W - 24Vdc - 1140lm - 3000K - CRI 90 -  
Cutttable every 62.5mm

GENERAL

Series: Brooklyn
Brand: Panzeri
Division: Architectural
Mounting Type: Trimless
Mounting Location: Ceiling
Subcategory: Profile

PHYSICAL

Shape: Rectangle
Length (mm): 500
Length (in): 19 11⁄16
Width (mm): 14
Width (in): 9⁄16
Light Distribution: Direct
Fixture Material: Aluminum

ELECTRICAL

Lamp Type: LED
Total Output Wattage (W): 8.6
Dimming: Non-Dimmable / 0-10V Dimming
Driver Included: No
Driver Location: Remote
Driver Type: Constant Voltage - Universal
Driver Class: Class 2
Input Voltage (V): 120 - 277
Output Voltage (V): 24

LED

Number of LEDs: 64
Color Temperature (°K): 3000
Max. Delivered Lumen (lm): 1140
CRI: >90 CRI

RATINGS AND CERTIFICATIONS

Certified By: Certified for North American Standards
IP rating: IP20





A8BROOK-TRI-SYS COMPONENTS TRIMLESS

A89117

**DESCRIPTION**  
LED module - 125mm - 2.15W - 24Vdc - 285lm - 3000K - CRI 90 -  
Cutttable every 62.5mm

**GENERAL**  
Series: Brooklyn  
Brand: Panzeri  
Division: Architectural  
Mounting Type: Trimless  
Mounting Location: Ceiling  
Subcategory: Profile

**PHYSICAL**  
Shape: Rectangle  
Length (mm): 125  
Length (in): 4 15/16  
Width (mm): 14  
Width (in): 9/16  
Light Distribution: Direct  
Fixture Material: Aluminum

**ELECTRICAL**  
Lamp Type: LED  
Total Output Wattage (W): 2.15  
Dimming: Non-Dimmable / 0-10V Dimming  
Driver Included: No  
Driver Location: Remote  
Driver Type: Constant Voltage - Universal  
Driver Class: Class 2  
Input Voltage (V): 120 - 277  
Output Voltage (V): 24

**LED**  
Number of LEDs: 16  
Color Temperature (°K): 3000  
Max. Delivered Lumen (lm): 285  
CRI: >90 CRI

**RATINGS AND CERTIFICATIONS**  
Certified By: Certified for North American Standards  
IP rating: IP20

PROJECT
TYPE
NOTES
QUANTITY
DATE



## A8BROOK-TRI-SYS COMPONENTS

PROJECT

TYPE

NOTES

QUANTITY

DATE

### LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

### IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

### IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)